

Carefree Satin Floor Polish

F2f

Description

A water based low gloss acrylic/styrene polymer emulsion floor finish


Key properties

Unique polymer technology from Johnson Diversey
Optimal blend of polymers, waxes resins and film formation ingredients
18 % solids
Matting agents to provide low Satin like gloss.

Benefits

- Hard wearing durable finish ideal for low maintenance areas
- Produces a low gloss finish ideal for enhancing natural floors such as Stone and Linoleum

Use instructions




Ensure old polish is removed
Apply only to a clean dry floor
Post Wet floor signs
Using a clean mop or applicator, charge with product and tamp down in a wringer, but do not wring out, the mop or applicator should be saturated but not dripping.
Apply to the floor using overlapping figure of 8 motion. On the first coat leave a 6 inch gap along edges.
Allow 20 – 30 minutes drying time. Ensure 1st coat is completely dry before applying a second coat, at right angles to the first coat applying product up to the edges. If required apply a 3rd coat in a similar manner.
Some floors such as stone, or worn porous linoleum/ vinyl will require sealing with Carefree Undercoat prior to application of Carefree Eternum
Regularly maintain the floor by damp mopping, machine scrubbing or spray cleaning. The ideal maintenance product for Carefree Emulsion is Carefree Maintainer.

Technical data

| | |
|-------------|-----------------------|
| Appearance: | Milky emulsion |
| pH neat | 8 - 9 |
| pH Diluted | Not Applicable |
| S.G. | 1.03 |
| Viscosity | 5 cps |

The above data is typical of normal production and should not be taken as a specification.



Carefree Satin

Safe handling and storage information

Store in original closed containers away from extreme temperatures.

Keep from freezing

Do not use at temperatures below 10 deg C

Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.

Product compatibility

Not suitable for unsealed wood. Some floors may require sealing prior to use e.g. Stone

Available pack sizes

2 x 5 L

Diversey Ltd

Weston Favell Centre

Northampton NN3 8PD

Tel. 0800 525 525

www.diversey.com