SAFETY DATA SHEET

HG liquid natural wax (HG product 65)



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name	: HG liquid natural wax (HG product 65)
Product code	: 260
Product description	: Consumer product.
Product type	: Liquid.
Other means of	:
identification	

1.2 Relevant identified uses of the substance or mixture and uses advised against Not applicable.

1.3 Details of the supplier of the safety data sheet

HG International BV Damsluisweg 70 - NL-1332 EJ - Almere - The Netherlands Tel.: +31 (0)36 54 94 700 - Fax: +31 (0)36 54 94 744 Email: info@hg.eu - Internet: www.hg.eu

e-mail address of person : safety@hg.eu responsible for this SDS

National contact

HG Hagesan UK Ltd. Unit 2 Lanswood Park Broomfield Road Elmstead Market Colchester Essex CO7 7FD Tel.: 0044 (0)1206 822744 Fax: 0044 (0)1206 827019

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number	: England and Wales NHS Direct: 0845 4647
	Scotland NHS 24: 08454 24 24 24
	Republic of Ireland 01 809 2166
Supplier	
Telephone number	: +31 (0)36 54 94 777
Hours of operation	: Mo-Fr 9.00-17.00
Information limitations	: Only for medical personnel.

1/12

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Europe

HG liquid natural wax (HG product 65)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture **Product definition** : Mixture Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Flam. Liq. 3, H226 STOT SE 3, H336 (Narcotic effects) Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Classification according to Directive 1999/45/EC [DPD] The product is classified as dangerous according to Directive 1999/45/EC and its amendments. Classification : R10 R66, R67 N; R51/53 Physical/chemical hazards : Flammable. Human health hazards 2 Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. **Environmental hazards** : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements		
Hazard pictograms		
Signal word	Danger	
Hazard statements	Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Foxic to aquatic life with long lasting effects.	
Precautionary statements		
General	f medical advice is needed, have product container or label at hand. Read labe before use.	;
Prevention	Keep away from heat/sparks/open flames/hot surfaces No smoking. Avoid preathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-vent area.	tilated
Response	F SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT nduce vomiting.	
Storage	Not applicable	
Disposal	Not applicable	
Hazardous ingredients	Naphtha (petroleum), hydrodesulfurized heavy	
Supplemental label elements	Repeated exposure may cause skin dryness or cracking.	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.	
Special packaging requirem		
Containers to be fitted with child-resistant fastenings	Yes, applicable.	
Tactile warning of danger	Yes, applicable.	

SECTION 2: Hazards identification

2.3 Other hazards

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

Substance/mixture : Mixture

			Classification		
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
Naphtha (petroleum), hydrodesulfurized heavy	EC: 265-185-4 CAS: 64742-82-1	>=75 - <90	R10 Xn; R65 R66, R67 N; R51/53	Flam. Liq. 3, H226 STOT SE 3, H336 (Narcotic effects) Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1]
			See Section 16 for the full text of the R- phrases declared above.	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid me	easures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Get medical attention immediately. Call a poison center or physician. Remove dentures if any. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

SECTION 4: First aid measures

4.2 Most important symptom Potential acute health effect	uts and a second s
Eye contact	No known significant effects or critical hazards.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
Over-exposure signs/symp	<u>toms</u>
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: Adverse symptoms may include the following: nausea or vomiting
4.3 Indication of any immedi	ate medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
SECTION 5: Firefighting	g measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.
media	
media	 Do not use water jet. Form the substance or mixture Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sew may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
media 5.2 Special hazards arising f Hazards from the	 From the substance or mixture Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sever may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and
media 5.2 Special hazards arising f Hazards from the substance or mixture Hazardous thermal	 Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sew may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. Decomposition products may include the following materials: carbon dioxide
media 5.2 Special hazards arising f Hazards from the substance or mixture Hazardous thermal decomposition products	 Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sew may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. Decomposition products may include the following materials: carbon dioxide

 Date of issue/Date of revision
 : 13-5-2015.
 Date of previous issue
 : No previous validation.

Version : 1 4/12

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	 No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and materials for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
6.4 Reference to other sections	 See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Europe

HG liquid natural wax (HG product 65)

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso II Directive - Reporting thresholds (in tonnes)

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b	5000	50000
E2: Hazardous to the aquatic environment - Chronic 2	200	500
C6: Flammable (R10)	5000	50000
C9ii: Toxic for the environment	200	500

7.3 Specific end use(s) Recommendations

: Not available.

Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection measure	<u>s</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

6/12

SECTION 8: Exposure controls/personal protection

Eye/face protection	Not applicable	
Skin protection		
Hand protection	Not applicable	
Body protection	When there is a risk of ignition from static electricity, wear anti-static protectiv clothing. For the greatest protection from static discharges, clothing should i anti-static overalls, boots and gloves. Refer to European Standard EN 1149 further information on material and design requirements and test methods.	nclude
Other skin protection	Not applicable	
Respiratory protection	Not applicable	
Thermal hazards	Not applicable	
Environmental exposure controls	Not applicable	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical	ar	nd chemical properties
<u>Appearance</u>		
Physical state	÷	Liquid.
Colour	÷	Yellow.
Odour	÷	Hydrocarbon.
Odour threshold	÷	Not available.
рН	÷	Not available.
Melting point/freezing point	1	26°C
Initial boiling point and boiling range	:	157 to 198°C
Flash point	:	Closed cup: 38°C
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Burning time	÷	Not applicable.
Burning rate	1	Not applicable.
Upper/lower flammability or explosive limits	1	Lower: 0,6% Upper: 6,5%
Vapour pressure	:	Not available.
Vapour density	1	Not available.
Relative density	1	0,775
Solubility(ies)	:	Partially soluble in the following materials: diethyl ether. Insoluble in the following materials: cold water and hot water.
Solubility in water	÷	Not available.
Partition coefficient: n-octanol/ water	1	Not available.
Auto-ignition temperature	:	210°C
Decomposition temperature	;	Not available.
Viscosity	;	Dynamic (room temperature): 250 mPa·s
Explosive properties	1	Not available.
Oxidising properties	;	Not available.

9.2 Other information

No additional information.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Europe

HG liquid natural wax (HG product 65)		
SECTION 10: Stability and reactivity		
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.	
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

SECTION 11: Toxicological information

11.1 Information on toxicological effects				
Acute toxicity Conclusion/Summary		Not available.		
Acute toxicity estimates				
Not available.				
Irritation/Corrosion				
Conclusion/Summary	:	Not available.		
Sensitisation				
Conclusion/Summary	:	Not available.		
<u>Mutagenicity</u>				
Conclusion/Summary	:	Not available.		
Carcinogenicity				
Conclusion/Summary	:	Not available.		
Reproductive toxicity				
Conclusion/Summary	:	Not available.		
Teratogenicity				
Conclusion/Summary	:	Not available.		
Specific target organ toxicit	<u>y (</u> s	<u>single exposure)</u>		

Product/ingredient name	Category	Route of exposure	Target organs
Naphtha (petroleum), hydrodesulfurized heavy	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure) Not available.

Aspiration hazard

Product/ingredient name	Result
Naphtha (petroleum), hydrodesulfurized heavy	ASPIRATION HAZARD - Category 1

Information on the likely	: Not available.
routes of exposure	
Detential coute health offecte	

Potential acute health effect	<u>ts</u>				
Eye contact	:	No known significant effects or critica	al hazards.		
Inhalation	:	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.			
Date of issue/Date of revision		: 13-5-2015. Date of previous issue	: No previous validation.	Version : 1	8/12

Conforms to Regulation (EC)	No. 1907/2006 (REACH), Annex II - Europe
	HG liquid natural wax (HG product 65)
SECTION 11: Toxicolog	ical information
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.
Symptoms related to the phy	vsical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: Adverse symptoms may include the following: nausea or vomiting
Deleved and immediate offer	
	ts and also chronic effects from short and long term exposure
Short term exposure	. Net eveileble
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary	: Not available.
General	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Other information	: Not available.

SECTION 12: Ecological information

12.1 Toxicity	
Conclusion/Summary	: Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Naphtha (petroleum), hydrodesulfurized heavy	-	10 to 2500	high

Date of issue/Date of revision

9/12

SECTION 12: Ecological information

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment		
PBT	:	Not applicable.
vPvB	÷	Not applicable.

12.6 Other adverse effects	s
----------------------------	---

dverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.
Packaging	
Methods of disposal	 The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number	1300	1300	1300	1300
14.2 UN proper shipping name	LDT QTY, TURPENTINE SUBSTITUTE of class 3", UN 1300, PG III, (+40°C c.c.), (White Spirit, 82%, mixture) (Naphtha (petroleum), hydrodesulfurized heavy)	LDT QTY, TURPENTINE SUBSTITUTE of class 3", UN 1300, PG III, (+40°C c.c.), (White Spirit, 82%, mixture) (Naphtha (petroleum), hydrodesulfurized heavy)	LDT QTY, TURPENTINE SUBSTITUTE of class 3", UN 1300, PG III, (+40°C c.c.), (White Spirit, 82%, mixture) (Naphtha (petroleum), hydrodesulfurized heavy). Marine pollutant (Naphtha (petroleum), hydrodesulfurized heavy)	LDT QTY, TURPENTINE SUBSTITUTE of class 3", UN 1300, PG III, (+40°C c.c.), (White Spirit, 82%, mixture) (Naphtha (petroleum), hydrodesulfurized heavy)
Date of issue/Date of re	vision : 13-5-2015.	Date of previous issue	: No previous validation.	Version : 1 10/12

HG liquid natural wax (HG product 65) SECTION 14: Transport information				
			14.3 Transport hazard class(es)	3
14.4 Packing group	Ш	Ш	III	Ш
14.5 Environmental hazards	No.	No.	Yes.	No.
Additional information	Hazard identification number 30	-	The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. <u>Emergency</u> <u>schedules (EmS)</u> F-E, S-E	The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for	: Transport within user's premises: always transport in closed containers that are
user	upright and secure. Ensure that persons transporting the product know what to do in
	the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

: Not determined.

: Not available.

Europe inventory Seveso II Directive

This product is controlled under the Seveso II Directive.

Danger criteria

Category P5c: Flammable liquids 2 and 3 not falling under P5a or P5b E2: Hazardous to the aquatic environment - Chronic 2 C6: Flammable (R10) C9ii: Toxic for the environment

Contains (Regulation (EC) : No 648/2004)

aliphatic hydrocarbons	>30%
aromatic hydrocarbons	5-15%
perfumes	

SECTION 15: Regulatory information

15.2 Chemical Safety	: This product contains substances for which Chemical Safety Assessments are still
Assessment	required.

SECTION 16: Other information

Indicates information that has changed from previously in the second	issued version.
--	-----------------

Abbreviations and acronyms : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	Expert judgment
STOT SE 3, H336 (Narcotic effects)	Expert judgment
Asp. Tox. 1, H304	Expert judgment
Aquatic Chronic 2, H411	Expert judgment

Full text of abbreviated H statements	 H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. (Narcotic effects) (Narcotic effects) H411 Toxic to aquatic life with long lasting effects. 	
Full text of classifications [CLP/GHS]	: Aquatic Chronic 2, H411LONG-TERM AQUATIC HAZARD - Category 2Asp. Tox. 1, H304ASPIRATION HAZARD - Category 1Flam. Liq. 3, H226FLAMMABLE LIQUIDS - Category 3STOT SE 3, H336SPECIFIC TARGET ORGAN TOXICITY (SINGLE(Narcotic effects)EXPOSURE) (Narcotic effects) - Category 3	
Full text of abbreviated R phrases	 R10- Flammable. R65- Harmful: may cause lung damage if swallowed. R66- Repeated exposure may cause skin dryness or cracking. R67- Vapours may cause drowsiness and dizziness. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. 	
Full text of classifications [DSD/DPD]	: Xn - Harmful N - Dangerous for the environment	
Date of printing	: 18-5-2015.	
Date of issue/ Date of revision	: 13-5-2015.	
Date of previous issue	: No previous validation.	
Version	: 1	
Notice to reader		

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.