



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name SHOE AND HELMET SPRAY

Product No. K259

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses non tainting residual sanitiser

1.3. Details of the supplier of the safety data sheet

Selden Research Limited t : 01298 26226 Staden Lane Ashbourne Road f : 01298 26540

Buxton Derbyshire SK17 9RZ United Kingdom

1.4. Emergency telephone number

01298 26226

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (67/548/EEC) F+;R12. N;R51/53. R67.

2.2. Label elements

Labelling



Dangerous for the En



e: safety@selden.co.uk

Extremely Flammable

Risk Phrases R12 Extremely flammable., R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment., R67 Vapours may cause drowsiness and dizziness.

Safety Phrases S2 Keep out of the reach of children.

S16 Keep away from sources of ignition - No smoking.

S23 Do not breathe vapour/spray. S51 Use only in well-ventilated areas.

2.3. Other hazards

No other hazards known

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not Applicable

3.2. Mixtures

ALIPHATIC HYDROCARBON

CAS-No.: 64741-84-0

Classification (EC 1272/2008)

Aspiration hazard, category 1 - H304

Classification (67/548/EEC)

Xn:R65

Aspiration hazard, category 1 - H304 Xn;R65
Flammable liquids, category 2 - H225 F;R11
Hazardous to the aquatic environment, chronic, category 2 - H411 N;R51/53
Hazardous to the aquatic environment, chronic, category 2 - H411

MSDS: K259 - SHOE AND HELMET SPRAY language: english Page 1 of 6







BUTANE CAS-No.: 106-97-8 EEC (EINECS) No. 203-448-7	10-30%
Classification (EC 1272/2008) Flammable liquids, category 1 - H224	Classification (67/548/EEC) F+;R12
PENTANE CAS-No.: 109-66-0 EEC (EINECS) No. 203-692-4	10-30%
Classification (EC 1272/2008) Flammable liquids, category 1 - H224 Aspiration hazard, category 1 - H304 STOT***, single exposure, category 3 - Narcotic effects - H336 Hazardous to the aquatic environment, chronic, category 2 - H411 Hazardous to the aquatic environment, chronic, category 2 - H411	Classification (67/548/EEC) F+;R12 Xn;R65 R66 R67 N;R51/53
Triclosan CAS-No.: 3380-34-5 EEC (EINECS) No.	0.5-1%
Classification (EC 1272/2008) Eye irritation, category 2 - H319 Skin irritation, category 2 - H315 Hazardous to the aquatic environment, acute, category 1 - H400 Hazardous to the aquatic environment, chronic, category 2 - H411	Classification (67/548/EEC) Xi;R36/38 N;R50/53

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Inhalation Move the exposed person to fresh air at once., Keep the affected person warm and at rest. Get prompt medical

attention., For breathing difficulties oxygen may be necessary.

Ingestion Rinse mouth thoroughly., Provide rest, warmth and fresh air.

Skin contact Wash the skin immediately with soap and water., Get medical attention if any discomfort continues.

Promptly wash eyes with plenty of water while lifting the eye lids., Continue to rinse for at least 15 minutes., Get Eye contact

medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Vapours may cause headache, fatique, dizziness and nausea., Prolonged inhalation of high concentrations

may damage respiratory system., High concentrations of vapours may irritate respiratory system and lead

to headache, fatigue, nausea and vomiting.

May cause burns in mucous membranes, throat, oesophagus and stomach., May cause stomach pain or Ingestion

vomiting

Skin contact Prolonged or repeated exposure may cause severe irritation., Acts as a defatting agent on skin. May cause

cracking of skin, and eczema.

Eye contact May cause severe irritation to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat Symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media Use:, Powder., Dry chemicals, sand, dolomite etc., Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Unsuitable extinguishing media

5.3. Advice for firefighters

Special Fire Fighting **Procedures**

Self contained breathing apparatus and full protective clothing must be worn in case of fire. Containers close to fire should be removed or cooled with water., Use water to keep fire exposed containers cool and disperse vapours.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

MSDS: K259 - SHOE AND HELMET SPRAY language: english Page 2 of 6





For personal protection, see section 8.

6.2. Environmental precautions

Any spillage needs to be contained and not allowed to enter water courses

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment., Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate., If leakage cannot be stopped, evacuate area.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame., Avoid spilling, skin and eye contact., Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

See product label for detailed usage and instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

 Name
 STD
 TWA - 8 Hrs
 STEL - 15 Min
 Notes

 BUTANE
 WEL
 600 ppm1450 mg/m3
 750 ppm1810 mg/m3

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Engineering measures Provide adequate general and local exhaust ventilation.

Hand protection Use protective gloves.

Eye protection Wear approved safety goggles.
Other Protection General workwear only

Hygiene measures DO NOT SMOKE IN WORK AREA!

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Comments Information given relates to total aerosol container contents.

Flash point (°C) - 74
Auto Ignition Temperature (°C) + 405
Flammability Limit - Upper(%) 1.8
Flammability Limit - Lower(%) 10.0

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Stable under normal temperature conditions., Avoid, Shocks and physical damage.

10.2. Chemical stability

MSDS: K259 - SHOE AND HELMET SPRAY language: english Page 3 of 6









Stable under normal temperature conditions., Avoid, Shocks and physical damage.

10.3. Possibility of hazardous reactions

None known

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

None known

10.6. Hazardous decomposition products

Fire creates:, Vapours/gases/fumes of:, Carbon monoxide (CO)., Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Toxicological information No toxicological data is available for this mixture, however data can be provided for specific raw materials upon

request.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea., Prolonged inhalation of high concentrations may

damage respiratory system., High concentrations of vapours may irritate respiratory system and lead to headache,

fatigue, nausea and vomiting.

Ingestion May cause burns in mucous membranes, throat, oesophagus and stomach., May cause stomach pain or vomiting.

Skin contact Prolonged or repeated exposure may cause severe irritation., Acts as a defatting agent on skin. May cause cracking

of skin, and eczema.

Eye contact May cause severe irritation to eyes.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Toxic to aquatic organisms., May cause long term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Degradability

The surfactants contained within the product comply with the biodegradability criteria as laid down in Regulation

(EC) No 648/2004.

12.3. Bioaccumulative potential

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility: The product contains substances, which are water soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

This product does not contain any PBT or PvB substances

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard., Dispose of waste and residues in accordance with local authority requirements.

MSDS: K259 - SHOE AND HELMET SPRAY language: english Page 4 of 6







SECTION 14: TRANSPORT INFORMATION

14.1. UN number

UN No. (ADR/RID/ADN) 1950 UN No. (IMDG) 1950 UN No. (ICAO) 1950

14.2. UN proper shipping name

AEROSOLS, FLAMMABLE Proper Shipping Name:

14.3. Transport hazard class(es)

ADR/RID/ADN Class

ADR/RID/ADN Class Class 2: Gases

2 1 IMDG Class ICAO Class/Division 2.1

Not Applicable Transport Labels

14.4. Packing group

14.5. Environmental hazards

Environmentally Hazardous substance/Marine Pollutant

14.6. Special precautions for user

Tunnel Restriction Code n/a

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

UK Regulatory References The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. **Environmental Listing** Rivers (Prevention of Pollution) Act 1961., Control of Pollution (Special Waste Regulations) Act 1980.

Control of Substances Hazardous to Health., The Chemicals (Hazard Information and Packaging for Supply) Statutory Instruments

Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice Classification and Labelling of Substances and Preparations Dangerous for Supply.

Workplace Exposure Limits EH40., Introduction to Local Exhaust Ventilation HS(G)37., CHIP for everyone HSG **Guidance Notes**

(108).

System of specific information relating to Dangerous Preparations. 2001/58/EC., Dangerous Preparations Directive 1999/45/EC., Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments., Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of

substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending

Regulation (EC) No 1907/2006 with amendments.

National Regulations The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007).

15.2. Chemical Safety Assessment

No chemical assessment has been carried out as this Safety Data Sheet is for a mixture

SECTION 16: OTHER INFORMATION

General information

EU Legislation

The following risk phrases relate to the raw materials in the product and not the product itself:-

Revision Comments

Safety Data Sheet revised to be in accordance with EU Regulation No 453/2010 - REACH Regulations.

08/06/2006 **Revision Date**

Revision 3

Risk Phrases In Full R12 Extremely flammable. | R12 Extremely flammable., R51/53 Toxic to aquatic organisms, may cause long-term

MSDS: K259 - SHOE AND HELMET SPRAY language: english Page 5 of 6







adverse effects in the aquatic environment., R66 Repeated exposure may cause skin dryness or cracking., R67 Vapours may cause drowsiness and dizziness., R65 Harmful: ma| R11 Highly flammable, R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment., R65 Harmful: may cause lung damage if swallowed.| R36/38 Irritating to eyes and skin., R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.|

Hazard Statements In Full	H224	Extremely flammable liquid and vapour.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

MSDS: K259 - SHOE AND HELMET SPRAY language: english Page 6 of 6