

Conforms to 2001/58/EC Issued: 17/10/2005

PRODUCT NAME: EXTEND AUTO-BURNISH MAINTAINER

I. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

 PRODUCT NAME
 : EXTEND AUTO-BURNISH MAINTAINER
 Product Number: 201

 PRODUCT USE
 : Water based floor coating maintainer

MANUFACTURER: Pioneer Eclipse Corp.

P.O.BOX: 909

ADDRESS: 1 Eclipse Road, Sparta, North Carolina, 28675, USA

PHONE: +1 336 372 8080

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/preparation: Preparation

INFORMATION ON HAZARDOUS INGREDIENTS

Chemical Name	Einecs No.	Weight %	CAS No.	Symbol	R-phrases *
Diethylene glycol monoethyl ether	203-919-7	5-10	111-90-0	Xi (irritant)	R36
Diethylene Glycol Methyl Ether	203-906-6	1-6	111-77-3	Xn (Harmful)	R63
Dibutyl Phthalate	201-557-4	1-3	84-74-2	T (Toxic) N (Dangerous to the Environment)	R50, R61, R62

^{*} see section 16 for the full text of relevant R-phrases

3. HAZARDS IDENTIFICATION

Physical/chemical hazards: No physical or chemical hazards have been reported or are known.

Human health hazards: This product is not dangerous according to the EU regulations (67/548/EEC-

1999/45/EC).

Environmental hazards: On the basis of available information this material/preparation is not

expected to produce any significant adverse environmental effects when

used as directed.

4. FIRST AID MEASURES

EFFECTS AND SYMPTOMS

Inhalation:None knownIngestion:None known

Skin contact: May be mildly irritating **Eye contact**: May be mildly irritating

FIRST AID MEASURES

Inhalation:No specific measures requiredIngestion:No specific measures required

Skin contact: Immediately wash off with plenty of water. If irritation develops, get medical

attention.

Eye contact: Immediately wash out with water. If irritation develops, get medical attention.



Conforms to 2001/58/EC Issued: 17/10/2005

PRODUCT NAME: EXTEND AUTO-BURNISH MAINTAINER

5. FIRE FIGHTING MEASURES

Extinguishing media: Dry chemical, water spray, foam, carbon dioxide

Hazardous combustion products: None

Unusual fire and explosion hazards: Materials can splatter above 100°C/212°F.

Special fire fighting procedures: None

6. ACCIDENTAL RELEASE MEASURES

Small spills: Absorb spill on inert material (e.g. sand, earth) and dispose of as waste material in

accordance with national and regional provisions.

Large spills: Keep spectators away. Floors may be slippery; use care to avoid falling. Dike and contain spill

with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills and cleaning runoff out of

sewers and open bodies of water.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes.

Storage: Storage temperature (Max. 60°C/140°F) (Min. 1°C/34°F). Keep from freezing, product may

coagulate. Keep container sealed when not in use. Keep out of reach of children.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Exposure limit values:

Component Name:	Source / Date	Value / Units	Type	Carcinogenic Listing*
Dibutyl Phthalate	US (ACGIH) / 2005	5 mg/m3	8 HRS / TWA	N/L
Dibutyl Phthalate	US (OSHA) / 2005	5 mg/m3	8 HRS / PEL TWA	

Exposure controls: No special ventilation requirements. Ensure adequate general ventilation.

OCCUPATIONAL EXPOSURE CONTROLS

Respiratory protection: No specific personal protection is required.

Hand protection: Rubber gloves recommended **Eye protection**: Safety glasses recommended

Skin protection: If major exposure is possible, wear suitable protective clothing such as

rubber boots, apron, etc.

Environmental exposure controls: No specific environmental exposure controls required.

9. PHYSICAL AND CHEMICAL PROPERTIES

GENERAL INFORMATION

Appearance: Thin milky white opaque liquid Odour: Slight ammonia



Conforms to 2001/58/EC Issued: 17/10/2005

PRODUCT NAME: EXTEND AUTO-BURNISH MAINTAINER

IMPORTANT HEALTH, SAFETY AND ENVIROMENTAL INFORMATION

pH: 8.35 to 8.85 Flash point: None

Oxidizing properties: Not an oxidizer Relative density: 1.04 kg/l @ 20°C

Solubility: 100% soluble (dispersible) in water **Partition coefficient (n-octanol/water)**: Not determined

Hazardous decomposition products: None known

Other information: forms a clear film upon drying

10. STABILITY AND REACTIVITY

Boiling point/boiling range: 100°C

Explosive properties: None Vapour pressure: Less than water

Viscosity: Less than 30 centipoise @ 20°C

Vapour density: Greater than air Evaporation rate: Less than water

11. TOXICOLOGICAL INFORMATION

COMPONENT SUMMARY

Conditions to avoid:

Materials to avoid:

Diethylene Glycol Ethyl Ether

LD₅₀: (Oral) rat 5.5 g/kg **LD**₅₀: (Skin) rabbit 9.0 g/kg

Potential Health Effects

Eye: May cause irritation to eyes. Symptoms include stinging, tearing, redness and swelling of eyes.

None known

None known

Skin: Mild skin irritation. May cause redness and burning of skin.

Ingestion: Small amount swallowed not likely to cause injury. Larger amounts may cause injury similar to

inhalation health effects. Also see below acute oral effects below.

Inhalation: Breathing small amounts not harmful but large amounts may be harmful. May cause dizziness or

drowsiness, central nervous system depression, nausea, headache, confusion or unconsciousness.

Chronic: May cause liver or kidney damage.

ACUTE ORAL EFFECTS:

Rat toxicity data (5.0 g/kg/day) indicates oxalate crystals in urine, degeneration of the liver and renal tubules, and transient dermatitis.

Repeated Dose Toxicity:

In a two year drinking water study with rats and mice no adverse effects were observed at 1% and 5%, respectively.

CARCINOGENICITY: Not expected to occur.

<u>Diethylene Glycol Methyl Ether</u>

 LD_{50} : (Oral) rat 7.1 g/kg, LD_{50} : (Skin) rabbit 9.4 g/kg

Potential Health Effects

Eye: May cause eye irritation. **Skin:** May cause skin irritation.

Ingestion: May cause irritation to mouth, nose and throat.

Inhalation: Irritating to respiratory system. **Chronic:** Possible risk to unborn child. **CARCINOGENICITY:** Not expected to occur.



Conforms to 2001/58/EC Issued: 17/10/2005

PRODUCT NAME: EXTEND AUTO-BURNISH MAINTAINER

Dibutyl Phthalate

LD₅₀: (Oral) rat 20 g/kg

Potential Health Effects

Eye: May cause eye irritation, splashes cause severe irritation with stinging pain and tears.

Skin: May cause skin irritation and possibly burns.

Ingestion: Irritation to gastrointestional tract such as nausea, vomiting and diarrhea.

Inhalation: May cause irritation to respiratory tract.

Chronic: May cause central nervous system toxicity. Possible risk of harm to the unborn child and possible

risk of impaired fertility.

CARCINOGENICITY: Not expected to occur.

PREPARATION SUMMARY

Acute Toxicity: LD₅₀ estimated to be greater than 2000 mg/kg

LOCAL EFFECTS

Skin contact: Irritating to skin upon repeated or prolonged contact.

Eye Contact:Slightly irritatingSensitization:None knownChronic effects:None known

SPECIFIC EFFECTS

Carcinogenicity: None known Reproductive effects: None known Teratogenicity: None known Mutagenicity: None known

12. ECOLOGICAL INFORMATION

COMPONENT SUMMARY

Diethylene Glycol Methyl Ether: not available

Dibutyl Phthalate

96 hr LC-50 (fathead minnow): 0.92 mg/l NOEC: 0.32 mg/l 96 hr LC-50 (bluegill sunfish): 0.48 mg/l NOEC: 0.42 mg/l

Diethylene Glycol Monoethyl Ether

Fathead Minnow; 96 hr; LC50 > 10000 mg/l

Preparation Summary

Ecotoxicity: This material is highly soluble in water. Limited toxicity tests and models indicate this

material should exhibit low toxicity to aquatic organisms.

Environmental fate: This material will biodegrade relatively rapidly in both soil and water, and will not

persist in the environment. Due care should be taken to avoid accidental releases to

aquatic or terrestrial systems.

Bioaccumulation: Because of this material's high solubility and rapid biodegradability, it is unlikely that

bioaccumulation will occur in aquatic or terrestrial systems. Models estimate that this material will preferentially partition to water versus air or soil. On the basis of

material will preferentially partition to water versus air or soil. On the basis of available information this material/preparation is not expected to produce any

significant adverse environmental effects, when used as directed.



Conforms to 2001/58/EC Issued: 17/10/2005

PRODUCT NAME: EXTEND AUTO-BURNISH MAINTAINER

13. DISPOSAL

Disposal of this material should be in accordance with local, regional, and national regulations.

14. TRANSPORT INFORMATION

INTERNATIONAL TRANSPORTATION REGULATIONS:

This product is not classified for transportation under ADR/IMDG regulations. **UN number**: not applicable **Packing group**: not applicable

LAND-ROAD/RAILWAY

Proper shipping name: not applicable
ADR/RID class: not applicable
ADR/RID item number: not applicable

SEA

Proper shipping name: not applicable IMDG class: not applicable

AIR

Proper shipping name: not applicable **ICAO class**: not applicable

Medical First Aid Guide (MFAG): not applicable Emergency Schedules (EmS): not applicable

Marine Pollutant: none

15. REGULATORY INFORMATION

NATIONAL REGULATIONS: No additional national regulations are known to the supplier.

EU REGULATIONS

EU Classification: Classified as non-hazardous according to current legislation (67/548/EEC,

1999/45/EC).

EINECS Status: All ingredients are included in the EINECS inventories.

CANADA CPR Status: This product has been classified in accordance with the hazard criteria of

the Controlled Products Regulations and the MSDS contains all the

information required by the Controlled Products Regulations.

16. OTHER INFORMATION

Relevant R-phrases

R36-Irritating to eyes.

R50-Very toxic to aquatic life.

R61-May cause harm to the unborn child.

R62-Possible risk of impaired fertility.

R63-Possible risk of harm to the unborn child.



Conforms to 2001/58/EC Issued: 17/10/2005

PRODUCT NAME: EXTEND AUTO-BURNISH MAINTAINER

Issued by:

Genie G Bost, Regulatory Affairs Manager

Revision Information:

17/10/2005, conforming to 2001/58/EC