

Carefree Eternum Floor Polish

F2e

Description

A durable water based acrylic/styrene polymer emulsion floor finish.

Key properties

Unique triple polymer technology from Johnson Diversey


22 % solids

Optimal blend of polymers, waxes resins and film formation ingredients

Benefits

- Superior Application properties and film formation
- Provides long lasting high gloss protection
- Excellent resistance to scuffs, marks and dirt
- Reduced maintenance costs.

Use instructions



Ensure old polish is removed

Apply only to a clean dry floor

Post Wet floor signs

Using a clean mop or applicator, charge with product and tamp down in a wringer, but do not wring out the mop or applicator should be saturated but not dripping

Apply to the floor using overlapping figure of 8 motion. On the first coat leave a 6 inch gap along edges.

Allow 20 – 30 minutes drying time. Ensure 1st coat is completely dry before applying a second coat. At right angles to the first coat applying product up to the edges. If required apply a 3rd coat in a similar manner.

Some floors such as stone, or worn porous/ vinyl will require sealing with

Carefree Undercoat prior to application of **Carefree Eternum**

Regularly maintain the floor by damp mopping, machine scrubbing or spray cleaning. The ideal maintenance product for **Carefree Eternum** is Carefree Maintainer.

Technical data

Appearance:

Milky emulsion

pH neat:

8 - 9

pH Diluted:

Not Applicable


S.G:

1.030

Viscosity:

Water thin

The above data is typical of normal production and should not be taken as a specification.



Carefree Eternum

Safe handling and storage information

Store in original closed containers away from extreme temperatures.

Keep from freezing

Do not use at temperatures below 10 ° C

Full guidance on the handling and disposal of this product is provided in a separate Material Safety Data Sheet.

Product compatibility

Suitable for hard floors including sealed Wood.

Some floors may require sealing with a porous floor sealer such as Carefree Undercoat for optimum results.

Approvals

Meets requirement of ASTM (James Machine) for slip resistance

Available pack sizes

2 x 5 L

Diversey Ltd

Weston Favell Centre

Northampton NN3 8PD

Tel. 0800 525 525

www.diversey.com