

# StanSolv AF-492

## DESCRIPTION AND GENERAL PROPERTIES

- Material Nitrile
- Length (inches) 12.5»
- Thickness (inches) 0.015» (15 mil)
- Wrist Straight cuff
- Colour/Color Green
- Interior finish Flocked
- Exterior finish Embossed texture
- Size / EAN 7 8 9 10 11
- Packaging 12 pairs/bag - 72 pairs/carton
- Complementary information Guaranteed without silicone



## PERFORMANCE RESULTS

Certification category 3

CE 0334



AJKL

4101

### Legends



**MECHANICAL HAZARDS**  
EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4

Abrasion resistance  
Blade cut resistance  
Tear resistance  
Puncture resistance



**LOW CHEMICAL PROTECTION**  
EN 374



**MICRO-ORGANISMS**  
EN 374



**RADIOACTIVE CONTAMINATION**  
EN 421



**SPECIFIC CHEMICAL PROTECTION**  
EN 374

Letter Code product

A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS**  
EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1

Convective cold resistance  
Contact cold resistance  
Water permeability



**HEAT AND FIRE**  
EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4

Burning behaviour  
Contact heat resistance  
Convective heat resistance  
Radiant heat resistant  
Resistance to small drops of molten metal  
Resistance to large quantities of molten metal

For more details: [www.mapa-pro.com](http://www.mapa-pro.com)

**MAPA**  
PROFESSIONAL  
[www.mapa-pro.com](http://www.mapa-pro.com)

# StanSolv AF-492

## DESCRIPTION AND GENERAL PROPERTIES

- Dexterity and comfort, due to the anatomical shape and the quality of the flock-lining
- Longer service life: excellent mechanical resistance (abrasion, perforation)

## MAIN FIELDS OF USE

### Automotive/mechanical industry

- Machining parts using cutting oil
- Treating/degreasing metals with solvents

### Chemical industry

- Manufacture and application of paints and varnishes

### Construction Industry (Carpenters/Joiners)

- Handling PVC-based glues
- Preparing coatings, varnishes

### Construction Industry (Masons / Plasterers)

- Cleaning tools
- Handling oils, solvents, detergents

### Construction Industry (Painters/Decorators)

- Cleaning
- Painting
- Scraping
- Varnishing

### Local Authorities (Catering Services)

- Cleaning ovens or worktops

### Local Authorities (Cleaning)

- Handling aggressive chemical products

### Local Authorities (Parks and Public Spaces)

- Plant Treatment Products

### Other industries

- Application of pesticides
- Cleaning of printing-press rollers
- Maintenance
- Timber treatment and finishing

## INSTRUCTIONS FOR USE

### Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- Persons sensitised to dithiocarbamates and thiazoles should not use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website [www.mapa-pro.com](http://www.mapa-pro.com) or contact the Technical Customer Service - MAPA PROFESSIONAL in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

### Storage conditions

Store the gloves in their original packaging protected from light, humidity and heat.

### Laundering conditions

Before taking off the gloves, clean them as appropriate :

- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
  - in use with a solvent (diluent, etc...) : rub over with a dry cloth
  - in use with acids or alkalis : thoroughly rinse the gloves under running water, and rub over with a dry cloth
- Caution : improper use of the gloves or submitting them to any cleaning or laundering process which is not specifically recommended can alter their performance levels.

**MAPA**<sup>®</sup>  
PROFESSIONAL  
[www.mapa-pro.com](http://www.mapa-pro.com)