

StanSolv AF-492

DESCRIPTION AND GENERAL PROPERTIES

- Material Nitrile
- Length (inches) 12.5»
- Thickness (inches) 0.015» (15 mil)
- Wrist Straight cuff
- Colour/Color Green
- Interior finish Flocked
- Exterior finish Embossed texture
- Size / EAN 7 8 9 10 11
- Packaging 12 pairs/bag - 72 pairs/carton
- Complementary information Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 3

CE 0334



AJKL

4101

Legends



MECHANICAL HAZARDS
EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4

Abrasion resistance
Blade cut resistance
Tear resistance
Puncture resistance



LOW CHEMICAL PROTECTION
EN 374



MICRO-ORGANISMS
EN 374



RADIOACTIVE CONTAMINATION
EN 421



SPECIFIC CHEMICAL PROTECTION
EN 374

Letter Code product

A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS
EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1

Convective cold resistance
Contact cold resistance
Water permeability



HEAT AND FIRE
EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4

Burning behaviour
Contact heat resistance
Convective heat resistance
Radiant heat resistant
Resistance to small drops of molten metal
Resistance to large quantities of molten metal

For more details: www.mapa-pro.com

MAPA
PROFESSIONAL
www.mapa-pro.com

StanSolv AF-492

DESCRIPTION AND GENERAL PROPERTIES

- Dexterity and comfort, due to the anatomical shape and the quality of the flock-lining
- Longer service life: excellent mechanical resistance (abrasion, perforation)

MAIN FIELDS OF USE

Automotive/mechanical industry

- Machining parts using cutting oil
- Treating/degreasing metals with solvents

Chemical industry

- Manufacture and application of paints and varnishes

Construction Industry (Carpenters/Joiners)

- Handling PVC-based glues
- Preparing coatings, varnishes

Construction Industry (Masons / Plasterers)

- Cleaning tools
- Handling oils, solvents, detergents

Construction Industry (Painters/Decorators)

- Cleaning
- Painting
- Scraping
- Varnishing

Local Authorities (Catering Services)

- Cleaning ovens or worktops

Local Authorities (Cleaning)

- Handling aggressive chemical products

Local Authorities (Parks and Public Spaces)

- Plant Treatment Products

Other industries

- Application of pesticides
- Cleaning of printing-press rollers
- Maintenance
- Timber treatment and finishing

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the «CE»-type tests.
- Persons sensitised to dithiocarbamates and thiazoles should not use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website www.mapa-pro.com or contact the Technical Customer Service - MAPA PROFESSIONAL in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

Storage conditions

Store the gloves in their original packaging protected from light, humidity and heat.

Laundering conditions

Before taking off the gloves, clean them as appropriate :

- in use with paints, pigments and inks : wipe with a clean cloth dampened with a suitable solvent, and rub over with a dry cloth
 - in use with a solvent (diluent, etc...) : rub over with a dry cloth
 - in use with acids or alkalis : thoroughly rinse the gloves under running water, and rub over with a dry cloth
- Caution : improper use of the gloves or submitting them to any cleaning or laundering process which is not specifically recommended can alter their performance levels.

MAPA[®]
PROFESSIONAL
www.mapa-pro.com