

Ultrane 553

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile
- **Length (inches)** 8.26-10.23 (depending on size)
- **Wrist** Knitted wrist
- **Colour/Color** Black
- **Interior finish** Seamless textile support
- **Exterior finish** Ventilated back
- **Size / EAN** 6 7 8 9 10
- **Packaging** 1 pairs/bag - 10 pairs/bag - 100 pairs/carton
- **Complementary information** Available in single pack and polybag of 10 pairs Guaranteed without DMF



PERFORMANCE RESULTS

Certification category 2



4121

Legends



MECHANICAL HAZARDS
EN 388

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4

Abrasion resistance
Blade cut resistance
Tear resistance
Puncture resistance



LOW CHEMICAL PROTECTION
EN 374



MICRO-ORGANISMS
EN 374



RADIOACTIVE CONTAMINATION
EN 421



SPECIFIC CHEMICAL PROTECTION
EN 374

Letter Code product

A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



COLD HAZARDS
EN 511

PERFORMANCE LEVELS

0-4 0-4 0 or 1

Convective cold resistance
Contact cold resistance
Water permeability



HEAT AND FIRE
EN 407

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4

Burning behaviour
Contact heat resistance
Convective heat resistance
Radiant heat resistant
Resistance to small drops of molten metal
Resistance to large quantities of molten metal

For more details: www.mapa-pro.com

MAPA
PROFESSIONAL
www.mapa-pro.com

Ultrane 553

DESCRIPTION AND GENERAL PROPERTIES

- Excellent abrasion resistance: longer-lasting
- Nitrile coating resistant to dirt particles
- Excellent tactile sensitivity and freedom of movement, due to the reduced thickness of the glove

MAIN FIELDS OF USE

Automotive/mechanical industry

- [Sorting small parts](#)
- Screwing and bolting
- Pump manufacturing
- Precision assembly

Other industries

- [Packaging](#)
- Minor maintenance Tasks
- Light handling in storage areas

Local Authorities (Technical Maintenance)

- [Small general maintenance jobs](#)

Construction Industry (Metalworkers/Locksmiths)

- [Handling and installing metal structures](#)

Construction Industry (Painters/Decorators)

- [Preparing surfaces](#)

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use in the workplace may differ from the tests performed in the laboratory.
- It is not recommended for persons sensitised to natural latex and dithiocarbamates.
- Put the gloves on dry, clean hands.
- Ensure the insides of the gloves are dry before putting them on again. Caution : using the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

Storage conditions

Store the gloves in their original packaging protected from heat, light and humidity.

LEGISLATION

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.

This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate

0075/014/162/12/04/0221

- Issued by the notified body nr

0075

CTC – F-69367 LYON CEDEX 07