

# Ultrane Performance 562

## DESCRIPTION AND GENERAL PROPERTIES

- **Material** Nitrile
- **Length (inches)** 8.25-10.24 (depending on size)
- **Wrist** Knitted wrist
- **Colour/Color** Black
- **Interior finish** Seamless textile support
- **Exterior finish** Dots
- **Size / EAN** 8 9 10
- **Packaging** 10 pairs/bag - 100 pairs/carton
- **Complementary information** Guaranteed without DMF



## PERFORMANCE RESULTS

Certification category 2



4121

### Legends



**MECHANICAL  
HAZARDS  
EN 388**

PERFORMANCE LEVELS

0-4 0-5 0-4 0-4  
 └─ Abrasion resistance  
 └─ Blade cut resistance  
 └─ Tear resistance  
 └─ Puncture resistance



**LOW CHEMICAL  
PROTECTION  
EN 374**



**MICRO-ORGANISMS  
EN 374**



**RADIOACTIVE  
CONTAMINATION  
EN 421**



**HEAT  
AND FIRE  
EN 407**

PERFORMANCE LEVELS

0-4 0-4 0-4 0-4 0-4 0-4  
 └─ Burning behaviour  
 └─ Contact heat resistance  
 └─ Convective heat resistance  
 └─ Radiant heat resistant  
 └─ Resistance to small drops of molten metal  
 └─ Resistance to large quantities of molten metal



**SPECIFIC CHEMICAL  
PROTECTION  
EN 374**

Letter Code	Chemical product
A	Methanol
B	Acetone
C	Acetonitrile
D	Dichloromethane
E	Carbon Disulfide
F	Toluene
G	Diethylamine
H	Tetrahydrofurane
I	Ethyl acetate
J	n-Heptane
K	Sodium hydroxide 40%
L	Sulphuric acid 96%



**COLD HAZARDS  
EN 511**

PERFORMANCE LEVELS

0-4 0-4 0 or 1  
 └─ Convective cold resistance  
 └─ Contact cold resistance  
 └─ Water permeability

For more details: [www.mapa-pro.com](http://www.mapa-pro.com)

**MAPA**  
PROFESSIONAL  
[www.mapa-pro.com](http://www.mapa-pro.com)

# Ultrane Performance 562

## DESCRIPTION AND GENERAL PROPERTIES

- Excellent abrasion resistance: longer-lasting
- Nitrile coating resistant to dirt particles
- Excellent tactile sensitivity and freedom of movement, due to the reduced thickness of the glove
- Back partially coated for improved protection

## MAIN FIELDS OF USE

### Automotive/mechanical industry

- [Sorting small parts](#)
- Screwing and bolting
- Pump manufacturing
- Precision assembly
- Metal part assembly

### Other industries

- [Packaging](#)
- Minor maintenance Tasks
- Light handling in storage areas

## INSTRUCTIONS FOR USE

### Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use in the workplace may differ from the tests performed in the laboratory.
- It is not recommended for persons sensitised to natural rubber latex or dithiocarbamates to use these gloves.
- Put the gloves on dry, clean hands.
- Rub over the gloves with a clean cloth before taking them off.
- Check the gloves for cracks or snags before reusing them.

### Storage conditions

Store the gloves in their original packaging protected from heat, light and humidity.

### Laundering conditions

Caution : improper use of the gloves or submitting them to a cleaning or laundering process that is not specifically recommended can alter their performance levels.

### Drying conditions

Ensure the inside of the gloves is dry before putting them on again.

## LEGISLATION

This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.

This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- CE-Type Examination Certificate  
0075/014/162/05/04/0073 Ex 01/05/04
  - Issued by the notified body nr  
0075
- C.T.C – F-69367 LYON CEDEX 07